




STARLINK GEN3 PERFORMANCE KIT


WHAT'S IN THE BOX?




Starlink Performance Dish




Advanced Power Supply




Starlink Performance Cable (25m)



Starlink Ethernet Cable (5m)



Starlink AC Power Cable (1.5m)



Starlink DC Power Cable (1.5m)

APPLICATIONS

Specifically engineered for resilient connectivity in remote areas and harsh environments. It excels in extreme weather conditions, ensuring reliable performance even in rain, snow, or intense heat. Additionally, its robust design withstands high-vibration settings and supports seamless connectivity during in-motion usage, making it ideal for challenging applications.

MOUNTS & ACCESSORIES

EnerStar Solutions provides mounting options for the Starlink Gen 3 Kit, suitable for installation on truck roofs for in-motion use or on roofs, poles, and walls to reduce obstructions. We offer accessories like cable routing kits, extended cable lengths, and access points to enhance your setup.

STARLINK SPECIFICATIONS

Package Weight	5.2 kg (11.5 lb)
Antenna	Electronic Phased Array
Field of View	140°
Orientation	Software Assisted Manual Orienting
Snow Melt Capability	Up to 85mm / hour (3.5 in / hour)
Operating Temperature	-40°C to 60°C (-40°F to 140°F)
Wind Speed	Survivable: 280 kph+ (174 mph+)
Power Consumption	Average: 75 - 100 W
Environmental Rating	IP69K (with cables installed) IP68 (no cables installed)
Router Compatibility	Starlink Gen3 Router Starlink Mini Mesh Router 3rd Party Routers

